



**PRODUCT CATALOGUE**

*We give you the extra mile*

- PRODUCT NAME**            **UNIOIL ATF**  
High Quality Automatic Transmission Fluid
- PERFORMANCE LEVEL**    DEXRON II
- APPLICATION**             Recommended for automatic transmission and power steering systems that require Dexron II type fluid
- BENEFITS**
- ◆ Superior oxidation stability
  - ◆ Compatibility to several types of oil seals
  - ◆ Good lubricating characteristics for smooth shifting and quiet operations
  - ◆ Effective anti-foam and anti-wear properties

**TYPICAL CHARACTERISTICS**

<b>TEST ITEMS</b>	<b>ASTM</b>	<b>Typical Data</b>
Appearance	Visual	clear
KINEMATIC VISCOSITY @40°C, cSt	D445	37.0-42.0
KINEMATIC VISCOSITY @100°C, cSt	D445	7.1 - 7.5
Viscosity Index	D2270	145 min
Flash Point °C, COC	D 92	200 min
TAN, mg/KOH/g	D 664	0.9 max
Color	D 1500	Cherry Red
Density @15°C, (g/cm <sup>3</sup> )	D 1298	0.8688 typ
Water Content, %vol.	D95	NIL

Distributed by Unioil Petroleum Philippines, Inc.  
Sta. Ana Office:  
2445 Pedro Gil St., Sta. Ana, Manila  
Tel No.:(632) 564-1991 Fax No. (632) 564 4486

Tektite Office:  
2701 West Tower PSE Center, Ortigas Center, Pasig City 1600, Philippines  
Tel No. (632) 687-8877 Fax No. (632) 631-2032

TDS Form No. UNPRODLUBE1  
Revision No.2  
Revision Date 3 July 2012