



PRODUCT CATALOGUE

We give you the extra mile

- PRODUCT NAME** **UNIOIL GMX SF**
High Performance Gasoline Engine Oil
- SAE GRADE** 20W-40
- PERFORMANCE** API: SF/CD
- APPLICATION** Recommended for gasoline engine in passenger cars, light trucks and 4 stroke motorcycles.
- BENEFITS**
- ◆ Improved anti-wear performance
 - ◆ Increased oxidation stability
 - ◆ Provides protection against rust and corrosion

TYPICAL CHARACTERISTICS

TEST ITEMS	ASTM	Typical Data
Appearance	Visual	clear
KINEMATIC VISCOSITY @40°C, cSt	D445	132.5 typ
KINEMATIC VISCOSITY @100°C, cSt	D445	14.3-16.1
Viscosity Index	D2270	100 min
Flash Point °C, COC	D 92	200 min
TBN, mg/KOH/g	D 2896	5.0 min
Color	D 1500	5.0 max
Density @15°C, (g/cm ³)	D 1298	0.8857
Water Content, %vol.	D95	NIL

Distributed by Unioil Petroleum Philippines, Inc.
Sta. Ana Office:
2445 Pedro Gil St., Sta. Ana, Manila
Tel No.:(632) 564-1991 Fax No. (632) 564 4486

Tektite Office:
2701 West Tower PSE Center, Ortigas Center, Pasig City 1600, Philippines
Tel No. (632) 687-8877 Fax No. (632) 631-2032

TDS Form No. UNPRODLUBE1
Revision No.2
Revision Date 3 July 2012