



PRODUCT CATALOGUE

We give you the extra mile

PRODUCT NAME **UNIOIL GMX SG**
High Performance Gasoline Engine Oil

SAE GRADE 20W-50

PERFORMANCE LEVEL API: SG/CD
US MILITARY L-2104E
VW 501.01 / 505.00
MERCEDES BENZ 226.5
CCMC

APPLICATION Recommended for gasoline engine in passenger cars, light trucks and 4 stroke motorcycles.

- BENEFITS**
- ◆ Improved control of engine deposits
 - ◆ Thermally stable
 - ◆ Increased oxidation stability
 - ◆ Better fuel economy
 - ◆ Provides engine wear protection

TYPICAL CHARACTERISTICS

TEST ITEMS	ASTM	Typical Data
Appearance	Visual	clear
KINEMATIC VISCOSITY @40°C, cSt	D445	148.75 typ
KINEMATIC VISCOSITY @100°C, cSt	D445	16.3-18.5
Viscosity Index	D2270	110 min
Flash Point °C, COC	D 92	200 min
TBN, mg/KOH/g	D 2896	5.0 min
Color	D 1500	5.0 max
Density @15°C, (g/cm ³)	D 1298	0.8852 typ
Water Content, %vol.	D95	NIL

Distributed by Unioil Petroleum Philippines, Inc.
Sta. Ana Office:
2445 Pedro Gil St., Sta. Ana, Manila
Tel No.:(632) 564-1991 Fax No. (632) 564 4486

Tektite Office:
2701 West Tower PSE Center, Ortigas Center,Pasig City1600,Philippines
Tel No. (632) 687-8877 Fax No. (632) 631-2032

TDS Form No. UNPRODLUBE1
Revision No.2
Revision Date 3 July 2012