



PRODUCT CATALOGUE

We give you the extra mile

PRODUCT NAME **UNIOIL 2T ECOPLUS**
Motorcycle Oil

SAE GRADE 30

PERFORMANCE TB

APPLICATION Developed for air-cooled two-stroke gasoline engines where the oil is mixed with fuel (motorcycles, lawnmowers, chainsaws, mopeds and small outboard engines). Suitable for use at fuel to oil ratios up to 25:1 or as specified by the equipment manufacturer.

BENEFITS

- ◆ Good miscibility with fuel ensuring homogeneous oil-fuel mixture
- ◆ Excellent protection against spark plug fouling, exhaust port blocking, scuffing wear, ring sticking, rust and corrosion
- ◆ Compatible with wet clutches
- ◆ Excellent detergency for much cleaner engine

TYPICAL CHARACTERISTICS

TEST ITEMS	ASTM	Typical Data
Appearance	Visual	clear
KINEMATIC VISCOSITY @40°C, cSt	D445	124.73 typ
KINEMATIC VISCOSITY @100°C, cSt	D445	9.3-12.4
Viscosity Index	D2270	88 typ
Flash Point	D92	200 min
Acid Number, mg/KOH/g	D 664	0.20 max
Color	D 1500	L3.0 typ
Density @15°C, (g/cm ³)	D 1298	0.8850

Distributed by Unioil Petroleum Philippines, Inc.
Sta. Ana Office:
2445 Pedro Gil St., Sta. Ana, Manila
Tel No.:(632) 564-1991 Fax No. (632) 564 4486

Tektite Office:
2701 West Tower PSE Center, Ortigas Center, Pasig City 1600, Philippines
Tel No. (632) 687-8877 Fax No. (632) 631-2032

TDS Form No. UNPRODLUBE1
Revision Date 3 July 2012

Revision No.2